

# ITC EP017: Safe Area Electric Driven Hydraulic Power Unit



## Equipment description:

The Electric Hydraulic Power Unit (EHPU) is mounted in a DNV 2.7-1 approved protection / lifting frame, which comes complete with lifting sling (single lift) and fork lift pockets.

The EHPU has been designed to provide hydraulic power to various types of hydraulic equipment.

The EHPU is operated by a user friendly control panel consisting of all shutdowns warnings and controls.



Degree of Protection:	Safe Area Only / IP56
Electric Motor Power Rating:	22kW @ 50Hz / 26kW @ 60Hz
Power Supply Required:	400v/3ph/50Hz / 460v/3ph/60Hz
Power Cable Length:	10 Metres
Lifting Method:	Certified DNV 2.7-1 Crash Frame + Slings, Fork Lift Pockets
Hydraulic System Type:	Open Loop
Pump Type:	Axial Piston Pump (Pressure compensated)
Max Displacement:	34cc/rev
Max Working Pressure:	210bar
Max Flow @ Max Pressure:	51L/min @ 210bar @ 50Hz- 60L/min @ 210bar @60Hz
Reservoir Oil Capacity/Type:	200 Litres / ISO 32 Hyd. Oil
Connections:	Pressure – 3/4" NPT Return – 1" NPT Case Drain – 1/2" NPT
Oil Cooling Method:	Blast Air cooler
Interconnecting Hoses:	Not supplied
Unit Dimensions (LxBxH):	1500 x 1010 x 1250 (mm)
Unit Gross Weight:	2100(kgs)